



**NATIONAL DECLARATION OF PERFORMANCE**  
**no 1/2024**

1. Name and trade name of the construction product:

**Chimney tape,**

2. Construction product type designation<sup>1</sup>):

**Kaproflex Plus**

3. Intended use or uses:

**Intended to ventilate the roof slope and protect the roof in the ridge area from insects, blowing snow and water.**

4. Name and address of the manufacturer's registered office and place of manufacture of the product:

**P.P.H.U. „KOMPLEX: s. c. S. Zagórski, Z. Zaława,  
Moskorzew 146, 29-130 Moskorzew**

5. The name and business address of the authorized representative, if appointed :

**Nie dotyczy**

6. National system used to assess and verify constancy of performance:

**4**

7. National technical specification :

7a. Polish product standard:

.....

Name of accredited certification body, accreditation number and national certificate number or name of accredited laboratory(s) and accreditation number<sup>2</sup>):

.....

7b. National technical assessment :

Technical Assessment Body/National Technical Assessment Body:

**National Technical Assessment ITB-KOT-2019/1224**

Name of accredited certification body, accreditation number and certificate number<sup>2</sup>):

**Instytut Techniki Budowlanej**

**Ul. Filtrowa 1, 00-611 Warszawa**



8. Declared performance characteristics:

Pos.	Essential characteristics	Performance characteristics of the chimney tape	Evaluation method
1	Strength of the joint tape - roofing on the wall, N/50mm: - Tape - clay tile - Tape - sheet metal	$\geq 80$ $\geq 55$	PN-EN 12317-2:2010
2	Peel strength of the tape-tile joint, N/50mm	$\geq 75$	
3	Joint strength of aluminum tape - fleece on the wall, N/50mm	--	
4	Properties of painted coatings on aluminum strips (a) nominal thickness of the painted coating, $\mu\text{m}$	$\geq 10$	PN-EN ISO 2808:2008 met. 7D
	(b) resistance to detachment from the substrate by the notch grid method, degree of	Evaluation of test result	PN-EN ISO 2409:2013
	(c) surface condition (appearance) determined by visual inspection of finished products: - blisters	No	Ocena wizualna
	- longitudinal marks	No	
	- pores imprints	No	
	- scratches and transverse folds	No	
	- uncovered sheet metal edges	No	
- Surface quality at points of articulation	No damage		

9. The performance characteristics of the product specified above are in accordance with all the listed in sec. 8 declared performance characteristics. This national declaration of performance is issued in accordance with the Law of April 16, 2004 on construction products, under the sole responsibility of the manufacturer.

On behalf of the manufacturer signed(s):

Przedsiębiorstwo Produkcyjno-Handlowo-Uslugowe.....  
*KOMPLEX* s.c.  
 (name and position)  
 29-130 MOSKORZEW, Moskorzew 146  
 Zakład Produkcyjny Zawada Pilicka 66, 42-446 I rzędzie  
 NIP 656-22-78-399, Regon 260222319.....

(place and date of issue) (signature)

1) In accordance with the national systems of assessment and verification of constancy of performance defined in § 4 of the Regulation of the Minister of Infrastructure and Construction of November 17, 2016 on the manner of declaring the performance of construction products and the manner of marking them with the construction mark (Journal of Laws, item 1966), the manufacturer determines the type of construction product for which he prepares a national declaration of performance. The method of marking such a defined type of construction product in the national declaration of performance shall be determined by the manufacturer. This marking should be linked to the product type, that is, to the set of levels or classes of performance and the intended use of the product, specified in the national declaration. The marking should be unique for the types of construction products produced by a given manufacturer.

2) Fill in if the certification body or laboratory/laboratories participated in the applied national system of assessment and verification of constancy of performance of the construction product.

3) If the provision of § 5 (1) (1) and (2) and (2) of this Regulation is applied, indicate in the third column which of the aforementioned provisions with respect to the essential characteristics of the product was applied.