

Declaration of Performance

No. 72.2/2013/L

Unique identification code of the product-type:	KAPROTEX MSL 115 AL MAX
Intended use/es:	Flexible sheets for waterproofing - Plastic vapour controls layers - EN 13984:2013
Manufacturer:	Steam-tight foil MSL 115 AL MAX Lenko S. A. Ul. Eugeniusza Kwiatkowskiego 42 43-365 Wilkowice lenko@lenko.com.pl Manufacturing plant Lenko S. A. Ul. Eugeniusza Kwiatkowskiego 42 43-365 Wilkowice
System/s of AVCP:	3
Harmonised standard: Notified body/ies:	EN 13984:2013 edition of 30.06.2013 NR. 1434

Declared performance

Essential characteristics	Performance	Harmonised technical specification
Unit area weight	115 +/- 15%	EN 13984:2013
Reaction to fire	F	
Watertightness	2 kPa	
Water vapour permeability	$360 \cdot 10^{-9}$ [m ² ·s·Pa/kg] +/-25%	
Impact resistance	NPD	
Join strenght	NPD	
Tensile properties, tensile force: - longitudinal direction - transverse direction Tensile properties: elongation: - longitudinal direction - transverse direction	≥450 [N/50mm] ≥ 400 [N/50mm] ≥10[%] ≥10[%]	
Tear resistance: - longitudinal direction - transverse direction	≥140[N] ≥140[N]	
Durability: - water vapour resistance after artificial ageing - water vapour resistance against alkali	positive result NPD	
Dangereous substances	NPD	

Signed for and on behalf of the manufacturer by:

"Lenko" Spółka Akcyjna
 43-365 Wilkowice, ul. E. Kwiatkowskiego 42
 Tel. 33/48-44-443 - Fax 33/81-22-202
 NIP 547-017-06-53 REGON 070478394
 BDO 000022792

"Lenko" Spółka Akcyjna
 Kierownik Technologii i Rozwoju

Justyna Grzybek

Wilkowice 28.08.2023