

## Declaration of Performance

No. 65.2 / 2023 /L

<b>Unique identification code of the product-type:</b>	<b>KAPROTEX ML 110</b>
<b>Intended use/es:</b>	<b>Underlays for discontinuous roofing - EN 13859-1:2010</b>
<b>Manufacturer:</b>	<b>Steam-Permeablefoil ML 110</b> Lenko S. A. Ul. Eugeniusza Kwiatkowskiego 42 43-365 Wilkowice lenko@lenko.com.pl  <b>Manufacturing plant</b> Lenko S. A. Ul. Eugeniusza Kwiatkowskiego 42 43-365 Wilkowice
<b>System/s of AVCP:</b>	3
<b>Harmonised standard: Notified body/ies:</b>	EN 13859-1:2010 edition of 22.09.2010 No. 1486 Centralny ośrodek Badawczo-Rozwojowy Przemysłu Izolacji Budowlanej No. 1454, Sieć Badawcza Łukasiewicz – Warszawski Instytut Technologiczny

### Declared performance

Essential characteristics	Performance	Harmonised technical specification
Unit area weight	110 +/- 15%	EN 13859-1:2010
Reaction to fire	F	
Resistance to water penetration	W3	
Tensile properties, tensile force: - longitudinal direction - transverse direction	300 +/- 180 [N/50mm] 230 +/- 180 [N/50mm]	
Tensile properties: elongation: - longitudinal direction - transverse direction	13+/-6[%] 13+/-6[%]	
Tear resistance: - longitudinal direction - transverse direction	200 +/- 140 [N] 205 +/- 145 [N]	
Artificial ageing behaviour concerning Tensile properties, tensile force: - longitudinal direction - transverse direction	300 +/- 210 [N/50mm] 230 +/- 170 [N/50mm]	
Tensile properties: elongation: - longitudinal direction - transverse direction	13+/-6[%] 13+/-6[%]	
Resistance to water penetration	W3	
Flexibility at low temperature	- 25°C	

Signed for and on behalf of the manufacturer by:

"Lenko" Spółka Akcyjna  
Kierownik Technologii i Rozwoju

Wilkowice 28.08.2023

Justyna Grzybek

"Lenko" Spółka Akcyjna  
43-365 Wilkowice, ul. E. Kwiatkowskiego 42  
Tel. 33/48-44-443 - Fax 33/81-22-202  
NIP 547-017-06-53 REGON 070478394  
BDO 000022792